

## CONTROL INFORMATION REWRITING SYSTEM

### CROSS REFERENCE TO RELATED APPLICATION

This application is based on and incorporates herein  
5 by reference Japanese Patent Application No. 11-347562 filed  
December 7, 1999.

### BACKGROUND OF THE INVENTION

10 This invention relates to an electronic control  
information rewriting system having nonvolatile memory with  
which electrical rewriting of data is possible, and particularly  
relates to technology for preventing the illegitimate rewriting  
of control information such as vehicle control programs or  
control data stored in the nonvolatile memory.

15 In electronic control units (ECUs) for controlling  
vehicle engines or the like, control information is stored in  
a nonvolatile memory with which electrical rewriting of data is  
possible. The control information includes programs and data  
and is rewritable even in the market after production.

20 For instance, this kind of ECU is constructed as shown  
in Fig. 9. A rewriting device 200 is connected to a vehicle 100  
via a vehicle diagnosis connector 120. A plurality of ECUs 101,  
102, 103 and 104 are mounted in the vehicle 100, and the ECUs  
101 through 104 are connected by a network line 110. The  
25 rewriting device 200 performs data communication with one of the  
four ECUs 101 through 104 by transmitting each ECU code on the  
basis of a manipulation of an operator.

In this system, as shown in Fig. 10, the rewriting device 200 selects the ECU 101, for instance, on which rewriting of control information is to be carried out, and transmits a rewriting request (b1). The selection of the ECU 101 is carried out by transmitting an ECU code. This ECU code is inputted to the rewriting device 200 by an operator. When this is done, the selected ECU 101 generates a random number  $r$  (b2), and transmits this random number  $r$  to the rewriting device 200 (b3).

A function  $f$  is pre-stored in the rewriting device 200, and it calculates a function value  $f(r)$  with respect to the transmitted random number  $r$  (b4). Then, it transmits this calculated function  $f(r)$  (b5). In the ECU 101, on the other hand, a function  $F$  is pre-stored, and a function value  $F(f(r))$  is calculated with respect to the transmitted function value  $f(r)$  (b6). Then, if the calculated  $F(f(r))$  corresponds to the random number  $r$ , that is if  $f=F^{-1}$ , it transmits a permission signal permitting rewriting (b7).

The above processing is for the ECU 101 to determine that the rewriting device 200 is legitimate when the rewriting device 200 has the inverse function  $f$  of the function  $F$  stored by the ECU 101.

The rewriting device 200, when receiving the permission signal transmitted from the ECU 101 (b8), transmits modification data. The ECU 101 carries out rewriting of control information on the basis of this modification data (b10). When the rewriting of control information completes normally, the ECU reports normal completion (b11), and the rewriting device

receives the report (b12) and one chain of rewriting processing ends.

In the above rewriting processing by communication processing (b1 through b7) using the function f, which is information inside the rewriting device 200, each ECU determines the legitimacy of the rewriting device 200. As a result, when the rewriting device 200 itself is stolen or information inside the rewriting device 200 is stolen, illegitimate rewriting of control information cannot be prevented. In particular, because the rewriting device 200 is provided, for instance, at a work site such as a car dealer, the possibility of the above theft is relatively high.

#### SUMMARY OF THE INVENTION

It is therefore an object of the present invention to prevent illegitimate rewriting of control information even when a rewriting device or information inside a rewriting device is stolen.

According to the present invention, a control information rewriting system has a control center as an external device for conducting data communication with a rewriting device. The control center could for example be installed in a different place from a rewriting work site. Access information is stored in the control center. Identification information and associated information are stored in the rewriting device. Identification information could be a number or the like unique to the rewriting device for identifying the rewriting device.

Associated information is information set in association with identification information.

For the legitimacy determination, the control center acquires the identification information and the associated information of the rewriting device in data communication with the rewriting device. Then, when an association relationship of the acquired information matches an association relationship, it transmits predetermined access information to the rewriting device. On the other hand, when it does not match, the predetermined access information is not transmitted to the rewriting device.

That is, the system attains the following two-stage checks.

[1] The control center determines the legitimacy of the rewriting device and transmits access information to the rewriting device.

[2] The rewriting device executes communication start processing using that access information, and each electronic control unit determines the legitimacy of the rewriting device on the basis of that communication start processing.

Thus, if at least either one of the identification information or the associated information is not pre-stored inside the rewriting device, the rewriting device cannot obtain access information from the control center. Therefore, if the rewriting device or information inside the rewriting device is stolen, it is not determined by the electronic control unit that the rewriting device is legitimate. Thus, rewriting of control

information is not carried out. As a result, even when the rewriting device or information inside the rewriting device is stolen, it is possible to prevent control information of an electronic control unit being improperly rewritten.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description made with reference to the accompanying drawings. In the drawings:

10

Fig. 1 is a block diagram showing a control information rewriting system according to an embodiment of the present invention;

Fig. 2 is an operation diagram showing rewriting processing in the embodiment;

Fig. 3 is a flow diagram showing a first half of ECU side processing in the embodiment;

Fig. 4 is a flow diagram showing a second half of ECU side processing in the embodiment;

Fig. 5 is a flow diagram showing a first half of rewriting device side processing in the embodiment;

Fig. 6 is a flow diagram showing a second half of rewriting device side processing in the embodiment;

Fig. 7 is a flow diagram showing a first half of control center side processing in the embodiment;

Fig. 8 is a flow diagram showing a second half of control center side processing in the embodiment;

Fig. 9 is a block diagram showing a control information rewriting system according to a related art; and

Fig. 10 is an operation diagram showing rewriting processing in the related art.

5

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

An embodiment of the present invention will now be described with respect to rewriting of vehicle control information.

10

Referring first to Fig. 1, a plurality of ECUs 11, 12, 13 and 14 are mounted in a vehicle 10, and the ECUs 11 through 14 are connected by a network line 15. The ECUs 11 through 14 have respective EEPROMs 11a through 14a which are nonvolatile type. At normal time, when a rewriting device 20 is not connected, on the basis of control information (control programs and control data) stored in this EEPROM, carry out communication between the ECUs 11 through 14 via the network line 15, and control respective control objects such as an engine.

15

20

In Fig. 1, the rewriting device 20 is shown as connected by way of a vehicle diagnosis connector 16 to the ECUs 11 so that a control information rewriting system 1 is formed. The vehicle diagnosis connector 16 is a connector provided on the vehicle 10 for making possible data communication between the rewriting device 20 and the ECUs 11 through 14 via the network line 15.

25

The vehicle 10 and the rewriting device 20 are installed in a work site such as a car dealer or repair shop.

In the control information rewriting system 1 of this

embodiment, the rewriting device 20 is capable of data communication via a telephone line network 40 with a control center 30. The control center 30 is installed as a so-called server as an external device in a different location from the work site. In a storage device (memory) 31 of this control center 30, access information for the rewriting device 20 to access the ECUs 11 through 14 with, modification data for rewriting or modifying control information, a database for determining the legitimacy of the rewriting device 20, and a database of control information update histories of different vehicles 10 are stored.

When the rewriting device 20 calls the control center 30, predetermined communication processing is carried out between the rewriting device 20 and the control center 30. The rewriting device 20 and the control center 30 assume a state such that data communication is possible. In Fig. 1, the control center 30 is shown as connected to a single rewriting device, but it is also conceivable for example for a rewriting device of a different work site to be connected to the control center 30 in parallel.

In this embodiment, the rewriting device 20 may be a portable personal computer which can be used for any types of vehicles. The control center 30 may be managed by a car manufacturer. The rewriting device 20 may be connected with the control center 30 by way of other means, for instance, cable TV network or wireless phone network, in place of ground telephone line network 40.

The operation of this control information rewriting system 1 is shown in block units B1 through B18. The processing in the ECUs 11 through 14 is shown as ECU side processing in a left side column in Fig. 2 as B5, B6, B9, B10, B15 and B16. The processing in the rewriting device 20 is shown as rewriting device side processing in a central column as B1, B4, B7, B8, B11, B14 and B17. The processing in the control center 30 is shown as control center side processing in a right side column as B2, B3, B12, B13 and B18. These processing are executed in the order B1 → B2 → B3 → ... → B18.

In operation, the rewriting device 20 first calls the control center 30. When a data communication possible state is established between the rewriting device 20 and the control center 30, the rewriting device 20 transmits to the control center 30 ID information as identification information for identifying the rewriting device 20 itself together with a communication start request (B1). With respect to this, the control center 30 receives the ID information from the rewriting device 20 and acquires the telephone number of the call origin, that is, the telephone number of the rewriting device 20 (B2). This telephone number is associated information.

The control center 30 has a database wherein the ID information of the rewriting device 20 and a telephone number assigned to the rewriting device 20 are associated. Accordingly, the control center 30 compares the association relationship between the received ID information and the acquired telephone number with an association relationship in the database (B2).



If they match, it transmits a first permission signal and a function  $f$  to the rewriting device 20 (B3).

The rewriting device 20 selects an ECU to be the object of control information rewriting from among the ECUs 11 through 14, and transmits a rewriting request to that ECU (B4). It is assumed here that the ECU 11 has been selected as the ECU to be the object of control information rewriting. The selected ECU 11 generates a random number  $r$  (B5) and transmits this random number  $r$  to the rewriting device 20 (B6).

The rewriting device 20, using the function  $f$  transmitted to it from the control center in B3 above, calculates a function value  $f(r)$  with respect to the random number  $r$  from the ECU 11 (B7). Then, it retransmits this calculated function value  $f(r)$  to the ECU 11 (B8).

On the other hand, a function  $F$  is pre-stored in the ECU 11, and with respect to the function value  $f(r)$  transmitted from the rewriting device 20 it calculates a function value  $F(f(r))$  (B9). Then, if the calculated function value  $F(f(r))$  corresponds to the random number  $r$ , that is if  $f = F^{-1}$ , it transmits a second permission signal permitting rewriting and transmits a vehicle VIN code (B10). The vehicle VIN code is a number assigned uniquely to each vehicle, and this corresponds to the above vehicle information.

The rewriting device 20 receives the second permission signal and the vehicle VIN code from the ECU 11 and transmits these information on to the control center 30 (B11).

The control center 30 has respective control

information update histories of each vehicle as a database. Accordingly, on the basis of the vehicle VIN code from the rewriting device 20, it carries out distinguishing of the vehicle 10, refers to the update history database, and determines the necessity of rewriting of control information (B12). When it determines that rewriting of control information to the vehicle 10 is necessary, it transmits modification data to the rewriting device 20 (B13).

The rewriting device 20 receives the modification data from the control center 30 and transmits this modification data to the ECU 11 (B14). The ECU 11, on the basis of the modification data from the rewriting device 20, performs rewriting of control information (B15). Then, if the rewriting of control information ends normally, it reports normal ending to the rewriting device 20 (B16). The rewriting device 20, when normal ending is reported from the ECU 11, erases the function f transmitted to it from the control center 30 in B3 above (B17). It reports normal ending to the control center 30. On the basis of this, the control center 30 updates the update history database (B18).

It is preferable that the functions  $f(r)$  and  $F(f(r))$  are differentiated from vehicle type to vehicle type from the standpoint of security.

For the above processing, the ECUs 11 through 14, the rewriting device 20 and the control center 30 are programmed to operate as shown in Figs. 3 through 8.

The ECU side processing executed in the ECUs 11 through 14 will be explained with reference to Figs. 2 and 3. This ECU

side processing is executed, with the rewriting device 20 connected by way of the vehicle diagnosis connector 16 to the vehicle 10, at a predetermined time interval such as for example 0.2 seconds.

5 First, at step (S) 300, it is determined whether or not there was a rewriting request from the rewriting device 20. When it is determined that there was a rewriting request (S300: YES), processing proceeds to S310. When on the other hand it is determined that there was not a rewriting request (S300: NO), this ECU side processing is terminated.

At S310, it is determined whether or not an access refusal timer is 0. The access refusal timer is set when it is determined a predetermined number of times in succession that the rewriting device 20 is not legitimate, as described above. When it is determined that the access refusal timer is not 0 (S310: NO), the timer is decremented at S320, and 0 is assigned to a variable C1, and this ECU side processing is terminated. The variable C1 counts the number of times in succession it is determined that the rewriting device is not legitimate. On the other hand, when it is determined that the access refusal timer is 0 (S310: YES), processing proceeds to S330.

At S330, it is determined whether or not the variable C1 is not greater than 2. When here  $C1 > 2$  (S330: NO), at S340 the access refusal timer is set and this ECU side processing is terminated. In this embodiment, 10 minutes is set. On the other hand, when  $C1 \leq 2$  (S330: YES), processing proceeds to S350.

At S350, a random number  $r$  is generated, and

transmitted to the rewriting device 20. This processing corresponds to the processing of B5 and B6 in Fig. 2. With respect to this, as shown in B8 in Fig. 2, a function value  $f(r)$  is transmitted from the rewriting device 20.

5           Accordingly, At the following S360, it is determined whether or not there was transmission of a function value  $f(r)$ . When here there was transmission of a function value  $f(r)$  (S360: YES), processing proceeds to S370. On the other hand, as long as there is no transmission of a function value  $f(r)$  (S360: NO), this determination processing is repeated.

          At S370, with respect to the function value  $f(r)$  transmitted from the rewriting device 20, a function value  $F(f(r))$  is calculated. This processing corresponds to the processing of B9 in Fig. 2.

          At the following S380 of Fig. 4, it is determined whether or not the calculated function value  $F(f(r))$  corresponds to the random number  $r$ . When here  $F(f(r)) = r$  (S380: YES), at S390 the second permission signal and the vehicle VIN code are transmitted, and processing proceeds to S420. The processing of S380 and S390 corresponds to the processing of B10 in Fig. 2. On the other hand, when  $F(f(r)) \neq r$  (S380: NO), it is reported at S400 to the rewriting device 20 that rewriting is not permitted, and at S410 the variable C1 is incremented and this ECU side processing is terminated. In this way the legitimacy of the rewriting device 20 is determined. When it is determined to be not legitimate (S380: NO), the variable C1 is incremented (S410), and at  $C1 > 2$  the timer is set as described above (S340

in Fig. 2). Thus, in this embodiment, when it is determined three times in succession that the rewriting device 20 is not legitimate, by C1 0 → 1 → 2, access refusal is carried out.

By the control center 30 a control information  
5 rewriting necessity determination based on the vehicle VIN code is carried out. If rewriting is necessary modification data is transmitted from the control center 30 via the rewriting device 20. On the other hand, if rewriting is not necessary, that is, when rewriting of control information has been carried out already, information indicating that rewriting has been done is transmitted from the control center 30 via the rewriting device  
10 20.

For this, at S420, it is determined whether or not there was data transmission from the rewriting device 20. When it is determined that there was data transmission (S420: YES),  
15 processing proceeds to S430. On the other hand, as long as there is no data transmission (S420: NO), this determination processing is repeated.

Then, at S430, it is determined whether or not the data  
20 transmitted from the rewriting device 20 is modification data. When it is determined that it is modification data (S430: YES), processing proceeds to S440. On the other hand, when it is determined that it is not modification data (S430: NO), that is, when information indicating that rewriting has been done was  
25 transmitted, the subsequent processing is not executed and this ECU side processing is terminated.

At S440, on the basis of the transmitted modification

data, rewriting of control information is carried out. At the following S450, a post-rewriting check sum of control information is calculated. This is for determining whether or not the control information was rewritten normally.

5           Then, at the next S460, on the basis of the check sum calculated at S450, it is determined whether or not the rewriting of control information ended normally. When it is determined that it ended normally (S460: YES), at S470 normal ending is reported to the rewriting device 20, and after that this ECU side processing is terminated. On the other hand, when it is not determined that it ended normally (S460: NO), at S480 the rewriting device 20 is requested to retransmit the modification data, and the processing from S420 is repeated.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235

following S510, it is determined whether or not there was a response from the control center 30. When it is determined that there was a response from the control center 30 (S510: YES), processing proceeds to S520. On the other hand, as long as there is no response from the control center 30 (S510: NO), this determination processing is repeated.

At S520, it is determined whether or not the response of the control center 30 is a report of non-permission. When it is determined that it is a report of non-permission (S520: YES), at S530 it is displayed on a display device such as a display that there has been a failure to access the control center 30. After that, the processing from S500 is repeated. On the other hand, when it is not a report of non-permission (S520: NO), that is, when the first permission signal and the function f have been transmitted, processing proceeds to S540.

At S540, the input of an ECU code for selecting one of the four ECUs 11 through 14 mounted in the vehicle 10 is requested of the operator. At the following S550, it is determined whether or not there was the input of an ECU code. When it is determined that there was the input of an ECU code (S550: YES), processing proceeds to S560. On the other hand, as long as there is no input of an ECU code (S550: NO), the processing from S540 is repeated. The following description will be continued assuming that the ECU code of the ECU 11 was inputted.

At S560, a rewriting request and the ECU code are transmitted. This processing corresponds to the processing of B4 in Fig. 2. On the basis of this, the ECU 11 generates a random

number r and transmits that random number r (S350 in Fig. 3).

Accordingly, at the following Step S570, it is determined whether or not a random number r has been transmitted. When it is determined that a random number r has been transmitted (S570: YES), processing proceeds to S580. On the other hand, as long as no random number r is transmitted (S570: NO), this determination processing is repeated.

At S580, using the function f transmitted from the control center 30 at S510, a function value  $f(r)$  specific to the random number r is calculated. At the next S590, the function value  $f(r)$  is transmitted to the ECU 11. This corresponds to the processing of B7 and B8 in Fig. 2.

With respect to this, in the ECU 11, an affirmative determination is made at S360 in Fig. 3, and the function value  $F(f(r))$  is calculated (S370). Then, on the basis of the determination of S380, transmission of a second permission signal or reporting that rewriting will not be permitted is carried out (S390, S400).

Accordingly, at the following S600 of Fig. 6, it is determined whether or not there was a response from the ECU 11. When it is determined that there was a response of the ECU 11 (S600: YES), processing proceeds to S610. On the other hand, as long as there is no response from the ECU 11 (S600: NO), this determination processing is repeated.

At S610, it is determined whether or not a second permission signal was transmitted from the ECU 11. When it is determined that a second permission signal was transmitted



(S610: YES), at S620 the second permission signal and the vehicle VIN code transmitted together with that second permission signal are transmitted to the control center 30, and after that processing proceeds to S640. This processing corresponds to the processing of B11 in Fig. 2. On the other hand, when a second permission signal was not transmitted (S610: NO), that is, when it was reported from the ECU 11 that rewriting will not be permitted, at S630 it is reported to the control center 30 that permission has not been given, and after that, processing proceeds to S530 in Fig. 5.

When at S620 the second permission signal and the vehicle VIN code are transmitted to the control center 30, the control center 30 determines the necessity of rewriting. If there is a need for rewriting, the control center 30 transmits modification data. On the other hand, if there is no need for rewriting, the control center 30 transmits information indicating that rewriting has been done.

Accordingly, at S640, it is determined whether or not there was a response from the control center 30. When it is determined that there was a response from the control center 30 (S640: YES), processing proceeds to S650. On the other hand, as long as there is no response (S640: NO), this determination processing is repeated.

At S650, it is determined whether or not the data transmitted from the control center 30 is modification data. When it was modification data (S650: YES), processing proceeds to S680. On the other hand, when it is not modification data

(S650: NO, that is, when information indicating that rewriting has been done was transmitted from the control center 30, the function f is erased and it is displayed that there is no need for rewriting (S660). Information indicating that rewriting has been done is transmitted to the ECU 11 (S670). This rewriting device side processing is then terminated.

At S680, the modification data transmitted from the control center 30 is transmitted to the ECU 11. This processing corresponds to the processing of B14 in Fig. 2. On the basis of this, in the ECU 11 rewriting of control information is carried out (S430 in Fig. 4: YES, S440), and a report of normal ending or a re-transmission request is transmitted from the ECU 11 (S470, 480).

Accordingly, at the next S690, it is determined whether or not there was a report of normal ending from the ECU 11. When it is determined that there was a report of normal ending (S690: YES), the function f is erased and normal ending is reported to the control center 30 (S700), and after that this rewriting device side processing is terminated. On the other hand, when there was not a report of normal ending (S690: NO), that is, when there was a request for re-transmission of the modification data, abnormal ending is reported to the control center 30 (S710) and this rewriting device side processing is terminated.

Continuing further, on the basis of the flow diagram of Fig. 7 and Fig. 8, the control center side processing executed by the control center 30 will be described. This control center side processing is executed, with a data communication possible

state established between the rewriting device 20 and the control center 30, at a predetermined time interval such as for example 0.2 seconds.

First, at S800, it is determined whether or not the access refusal timer is 0. The access refusal timer is set when it is determined a predetermined number of times in succession by the control center 30 that the rewriting device 20 is not legitimate, as will be further discussed later. When it is determined that the access refusal timer is not 0 (S800: NO), at S810 the timer is decremented. Further, 0 is assigned to a variable C2, and this control center side processing is terminated. The variable C2 counts the number of times in succession it is determined by the control center 30 that the rewriting 20 is not legitimate. On the other hand, when it is determined that the access refusal timer is 0 (S800: YES), processing proceeds to S820.

At S820, it is determined whether or not the variable C2 is not greater than 2. When here  $C2 > 2$  (S820: NO), at S830 the access refusal timer is set, and after that, this control center side processing is terminated. On the other hand, when  $C2 \leq 2$  (S820: YES), processing proceeds to S840.

At S840, it is determined whether or not there was a communication start request. This processing is specific to the processing of S500 in Fig. 5. When it is determined that there was a communication start request (S840: YES), processing proceeds to S850. On the other hand, as long as there is no communication start request (S840: NO), this determination

processing is repeated.

At S850, the ID information transmitted from the rewriting device 20 is received and the telephone number of the call origin is acquired. At the following S860, the association relationship between the received ID information and the acquired telephone number is compared with the association relationship between the ID information and the telephone number of the rewriting device 20 pre-stored in the database. The processing of these S850 and S860 corresponds to the processing shown in B2 of Fig. 2.

Then, at the next S870, on the basis of the comparison result, it is determined whether or not the association relationships match. When it is determined that they matched (S870: YES), at S890 the first permission signal and the function f are transmitted, and after that, processing proceeds to S900. This processing corresponds to the processing of B3 in Fig. 2. On the other hand, when it is determined that they did not match (S870: NO), it is reported to the rewriting device 20 that rewriting will not be permitted, and the variable C2 is incremented (S880), and after that, the processing from S800 is repeated.

The processing of S850 to S890 explained here corresponds to processing serving as legitimacy determining means. Therefore, the CPU of the control center 30 thus executes legitimacy determination.

When the first permission signal and the function f are transmitted, the rewriting device 20 transmits back the second

permission signal and the vehicle VIN code (S620 in Fig. 6), or reports the non-permission of rewriting (S630).

Accordingly, at S900, it is determined whether or not there was a response from the rewriting device 20. When it is determined that there was a response from the rewriting device 20 (S900: YES), processing proceeds to S910 in Fig. 8. On the other hand, as long as there is no response from the rewriting device 20 (S900: NO), this determination processing is repeated.

At S910, it is determined whether or not that response is a report of non-permission. When it was a report of non-permission (S910: YES), processing proceeds to S800 in Fig. 7. On the other hand, when it is not a report of non-permission (S910: NO), that is when the second permission signal and the vehicle VIN code were transmitted, processing proceeds to S920.

At S920, distinguishing of the vehicle is carried out on the basis of the transmitted vehicle VIN code, and the update history database is referred to. Then, at the next S930, on the basis of the reference result, it is determined whether or not there is a need to rewrite control information. The processing of these S920 and S930 corresponds to B12 in Fig. 2. When it is determined that there is a need of rewriting (S930: YES), processing proceeds to S950. On the other hand, when it is determined that there is no need of rewriting (S930: NO), at S940 information indicating that rewriting has been done is transmitted, and after that, this control center side processing is terminated.

At S950, modification data is searched for and read

out, and the modification data read out is transmitted to the rewriting device 20. This processing corresponds to the processing of B13 in Fig. 2. After that, from the rewriting device 20, as described above there is a report of normal ending (S700 in Fig. 6) or a report of abnormal ending (S710).

Accordingly, at S960, it is determined whether or not there was an ending report from the rewriting device 20. When it is determined that there was an ending report (S960: YES), processing proceeds to S970. On the other hand, as long as there is no ending report (S960: NO), this determination processing is repeated.

At S970, it is determined whether or not the ending report is a report of normal ending. When it is determined that it is a report of normal ending (S970: YES), at S980 the update history database is updated, and after that, this control center side processing is terminated. On the other hand, when it is determined that it is not a report of normal ending (S970: NO), that is, when it was a report of abnormal ending, the processing from S950 is repeated.

According to the above embodiment, the function f constituting access information is stored in the control center 30. Only when the control center 30 determines the rewriting device 20 to be a legitimate one, the function f is transmitted from the control center 30 to the rewriting device 20 (B2, B3 in Fig. 2). Therefore, even when the rewriting device 20 or information inside the rewriting device 20 is stolen, the access information for accessing the ECUs 11 through 14 is not stored

in the rewriting device 20. Therefore, it is not possible to rewrite the control information of the ECUs 11 through 14, if it is not possible to obtain access information from the control center 30.

5           The control center 30 has a database in which ID information uniquely assigned to the rewriting device 20 and a telephone number of the rewriting device 20 side of when data communication is to be carried out via a telephone line are stored in association. It acquires ID information from the rewriting  
10 device 20 and acquires the telephone number from which the call was made (S850 in Fig. 7). When the association relationship between this ID and telephone number matches the association relationship stored in the database (S860, S870: YES), the control center 30 determines that the rewriting device 20 is  
15 legitimate and transmits the function f, which is access information (S890). For example when a line is connected between the rewriting device 20 and the control center 30 from other than a regular work site, the telephone number that the control center 30 acquires ceases to be the pre-decided telephone number.  
20 Consequently, it does not correspond with the ID information, and the access information cannot be obtained from the control center 30. As a result, it is not possible to rewrite the control information in the ECUs 11 through 14.

25           As described above, with the control information rewriting system 1 of this embodiment, even when the rewriting device 20 or information inside the rewriting device 20 is stolen, control information of the ECUs 11 through 14 being

improperly rewritten can be certainly prevented.

With the control information rewriting system 1 of this embodiment, the control center 30 firstly determines the legitimacy of the rewriting device 20 and then the ECUs 11 through 14 determine the legitimacy of the rewriting device 20. When in either of these checks of two stages it is determined three times in succession that the rewriting device 20 is not legitimate, a ten minute access refusal is carried out.

That is, in the ECUs 11 through 14, when it is determined that the rewriting device 20 is not legitimate (S380: NO in Fig. 4), the variable C1 is incremented (S410). When the variable C1 becomes larger than 2 (S330: NO in Fig. 3), that is, when a determination of not legitimate is made three times in succession, an access refusal timer is set (S340). Thus, access of the rewriting device 20 is refused (S310: NO) until the timer becomes 0.

Meanwhile, similarly in the control center 30 also, when it is determined that the rewriting device 20 is not legitimate (S870: NO in Fig. 7), the variable C2 is incremented (S880). When the variable C2 becomes larger than 2 (S820: NO), that is, when a determination of not legitimate is made three times in succession, an access refusal timer is set (S830). Thus, access of the rewriting device 20 is refused (S800: NO) until the timer becomes 0.

As a result, even when an attempt is made to access the control center 30 or the ECUs 11 through 14 from the rewriting device 20 using illegitimate information, the control



information rewriting prevention can be prevented. Because it is not possible to access many times in succession, for the reason that access becomes impossible for ten minutes, if illegitimate access is carried out three times in succession.

5 In this embodiment, the control center 30 stores modification data of control information. That is, because modification data is not stored in the rewriting device 20 as in the past, even when the rewriting device 20 or information inside the rewriting device 20 is stolen, there is no possibility of modification data leaking to outside.

10 The control center 30 transmits modification data (S950) with a second permission signal from the ECUs 11 through 14 having been transmitted to it as one condition (S910: NO). That is, it transmits modification data with it having been determined by the ECUs 11 through 14 that the rewriting device 15 20 is legitimate as a condition. Therefore, the possibility of modification data leaking to outside is further reduced.

20 When the ECUs 11 through 14 determine that the rewriting device 20 is legitimate (S380: YES in Fig. 4), in addition to the second permission signal, they transmit a vehicle VIN code with which it is possible to specify the vehicle 10 (S390). The control center 30 has a database of update histories of control information stored in the ECUs 11 through 14 of different vehicles 10, and on the basis of the above-mentioned vehicle VIN code from the ECUs 11 through 14, distinguishes the 25 vehicle 10 and refers to the database (S920 in Fig. 8) and determines the necessity of control information rewriting

(S930). Then, when there is a need of rewriting (S930: YES), it transmits the modification data (S950).

In this embodiment, because the control center 30 manages the control information update histories of vehicles 10, futile rewriting of control information is not carried out. As a result, futile work time is not needed, and it ceases to happen that a necessary rewriting becomes impossible due to futile rewriting.

In the control center 30, when normal ending of rewriting is reported from the ECUs 11 through 14 via the rewriting device 20 (S970: YES in Fig. 8), the control information update history database is updated automatically (S980). Thus, there is no need for an operator to update the database by a manual operation.

In the rewriting device 20, when the function f constituting access information ceases to be needed (S650: NO, S690: YES in Fig. 6), that function f constituting access information is swiftly erased (S660, S700). Because of this, the possibility of the function f serving as access information transmitted from the control center 30 to the rewriting device 20 being stolen from the rewriting device 20 can be reduced.

This invention is not limited in any way to the disclosed embodiment, but may be implemented in other ways without departing from the spirit of the invention as follows.

(1) The control center 30 may have a database wherein the ID information of rewriting devices 20 and passwords are associated, and the rewriting device 20 may transmits a password

inputted by an operator together with the ID information. In this case, the password corresponds to associated information, and the control center 30 determines the legitimacy of the rewriting device 20 on the basis of the correspondence between the ID information and the password transmitted from the rewriting device 20.

The ID information may also be inputted from a user in the same way as the password. If this is done, even when the rewriting device 20 or information inside the rewriting device 20 is stolen, because the password or the ID information and the password are not known, it is not possible to obtain access information from the control center 30, and it is possible to prevent the improper rewriting of control information in the same way as in the embodiment described above.

However, because there is also a possibility of the ID information or the password being stolen by some other route, it is preferable for a telephone number connected with the installation site of the rewriting device 20 to be made associated information as in the embodiment described above. This is because improper rewriting is not carried out at a regular work site.

(2) It is conceivable for data communication between the control center 30 and the rewriting device 20 to be ended temporarily after the rewriting device 20 acquires the access information from the control center 30. For example, it is conceivable for data communication to be temporarily ended after the data communication of B1 through B4 in Fig. 2 finishes and

for a data communication possible state between the rewriting device 20 and the control center 30 to be re-established when the processing of B11 onwards is carried out.

However, there is a possibility of access information transmitted to the rewriting device 20 being stolen and the ECUs 11 through 14 being accessed using this access information, using a different rewriting device.

Therefore, it is beneficial if the control center 30 and the rewriting device 20 being in a data communication possible state is made a condition of rewriting until the chain of rewriting processing (the processing of B1 through B18 shown in Fig. 2) ends.

Specifically the following kind of construction could be adopted. That is, the rewriting device 20 may regularly transmit a response request to the control center 30 on the basis of timer interrupt processing or the like, and the control center 30 may perform a response. At this time, when there has ceased to be a response from the control center 30 before the chain of rewriting processing completes, the rewriting device 20 does not perform rewriting of the ECUs 11 through 14. If this is done, it becomes impossible to access an ECU from a different rewriting device using stolen access information.

(3) In the case where control programs stored in the ECU 11 becomes out of order for some reason, the processing shown in Fig. 2 should be modified so that such control programs may be rewritten.

In this instance, after executing B1 through B9 in Fig.

2, the ECU 11 reads out check sum of its control program and transmits it to the rewriting device 20 along with the second permission signal and the VIN code (B10). The rewriting device 20 transmits those received information to the control center 30 (B11). The control center 30 determines whether it is necessary to rewrite the control program based on the comparison of VIN code and check sum between the received ones and the pre-stored ones (12). Specifically, the control center 30 determines the version of the control program in the ECU 11 based on the received VIN code and determines whether the control program is normal by checking the received check sum of the control program. If the check sum differs from the pre-stored value, it determines that the control program is out of order or broken.

If the control center 30 determines based on the VIN code that the version of the control program has been changed, it transmits the modification data to the rewriting device 20 irrespective of the check sum determination result (B13). If the control center 30 determines that the version of the control program has not been changed but the control program is out of order, it transmits the original control program to the rewriting device 20. Thus, the control program in the ECU 11 can be renewed. It is of course possible to use key words or the like provided within the control program in place of using the check sum for detecting whether the control program has become out of order.